

KENWOOD

Listen to the Future

NEW PRODUCT INFORMATION

NEXEDGE™

NX-200/300

NEXEDGE™ VHF/UHF Digital & FM Portable Radios

NXDN™

FleetSync®
by KENWOOD

● GENERAL FEATURES

- 5 W (136-174 MHz) Models
- 5 W (450-520 MHz) Models
- 512 CH-GID / 128 Zones
- 12-Key Keypad Models
- 14 Character Alphanumeric Aliases
- Backlit Dot Matrix LCD
- 3-Digit Sub-Display
- Function/Status LCD Icons
- RSSI Indicator
- Date & 12/24 Hour Time Clock
- Transmit/Busy/Call Alert/Warn LED
- On/Off Volume Knob
- 16-Position Mechanical Selector
- 6 Front PF & Menu Keys
- 2 Side PF Keys
- Emergency/AUX Key
- 500 mW Speaker Audio
- VOX Ready
- Emergency Call Features
- Emergency Man-Down Option
- Special Alert Tone Patterns
- Time Out Timer
- Busy Channel Lockout
- LCD Battery Status Indicator
- Low Battery Alert
- Battery Saver
- Weather-sealed ACC Connector
- MIL-Spec Speaker Mic Options
- KMC-38GPS Speaker Mic Option
- KPG-111D Windows® FPU
- Flash Firmware Upgrading
- Front Panel Test & Tune
- Cloning
- MIL-STD-810 C/D/E/F
- MIL-STD "Driven-Rain"
- IP-54/55 Water & Dust Intrusion
- Easy Option Port
- Intrinsically Safe Option*
- VGS-1 Voice Guide/Storage Option*

● DIGITAL – GENERAL

- NXDN™ Digital Air Interface
- AMBE+2™ VOCODER
- 6.25 & 12.5 kHz Channels
- Over-the-Air Alias
- Paging Call
- Emergency Call
- NXDN™ Scrambler
- Status Messaging*
- Remote Stun/Kill*
- Short & Long Data Messages*
- GPS Location with Voice*

● DIGITAL – CONVENTIONAL MODE

- 63 Radio Access Numbers (RAN)
- Individual & Group Selective Call
- Mixed FM/Digital Operation

● DIGITAL – TRUNKING MODE

- Individual Private Call
- Group Call
- Priority Monitor ID 1 & 2
- Late Entry
- Broadcast Call
- Remote Group Add*
- Multi-Site IP Network Compatible*

● SCAN TYPES (FM & NXDN™ CONVENTIONAL)

- Single/Multi-Zone Scan
- Conventional Scan
- List Scan
- Dual Priority Scan

● FM MODES – GENERAL

- 25 & 12.5 kHz Channels
- FleetSync®/II
- DTMF Encode / Decode
- Companded Audio
- Voice Inversion Scrambler
- Encryption/ANI Board Control*

● FM CONVENTIONAL ZONES

- QT / DQT
- Two-Tone Decode
- Single/Two-Tone Encode
- Call Key 1-5
- Operator Selectable Tone

● FM LTR® TRUNKED ZONES

- Kenwood LTR® Features

● FleetSync®/II (FM)

- PTT ID Digital ANI
- Selective Call & Group Call
- Status Messaging
- Emergency Status
- Caller ID Display
- Short Text Messages
- Power On/Off Status Messages
- Send/Display GPS (KMC-38GPS)
- PTT ID & Emergency GPS Reporting
- Status Message Block GPS Reporting
- VGS-1 GPS Data Storage
- PC Serial Interface

* Some features/options are available in future releases.



KenwoodLandMobileRadio
25Years

Options

KNB-47L
Li-Ion Battery
(1950mAh)



KNB-48L
Li-Ion Battery
(2550mAh)



KSC-32
Tri-Chemistry Rapid
Rate Charger



KMC-25
Microphone

KHS-11
Heavy Duty Earphone



KEP-1
Heavy Duty Earphone



KCT-48VU
Vibration Adaptor



KRA-22/23
VHF/UHF Helical Antenna



KRA-26/27
VHF/UHF Whip Antenna



KRA-16/17
VHF/UHF Stubby Antenna



KRA-25
VHF High Gain Antenna



KRA-28
VHF Broad
Band Antenna



VGS-1
Voice Guide
& Storage Unit



KBH-11
Belt Clip (2.5")



All accessories and options may not be available in all markets. Contact an authorized Kenwood dealer for details and complete list of all accessories and options.

Main Specifications

		NX-200	NX-300
GENERAL			
Models	Basic Model w / 12 key	NX-200K NX-200K2	NX-300K NX-300K3
Frequency Range		136-174 MHz	450-520 MHz
Number of Channels		512	
Zones		128	
Max. Channels per Zone		250	
Channel Spacing	Analog	12.5 / 15 / 25 / 30 kHz	12.5 / 25 kHz
	Digital	6.25 / 12.5 kHz	6.25 / 12.5 kHz
Operating Voltage		7.5V DC ± 20%	
Battery Life (with KNB-48L)	5-5-90	More than 12.5 hours	
	10-10-80	More than 8.5 hours	
Operating Temperature Range		-22° F to +140° F (-30° C to +60° C)	
Frequency Stability		± 2.0 ppm	± 1.0 ppm
Antenna Impedance		50 Ω	
Dimensions (W x H x D)	Projections not included		
	Radio only	2.28 x 5.02 x 1.63 in (58 x 127.5 x 41.3 mm)	
	with KNB-47L	2.28 x 5.02 x 1.63 in (58 x 127.5 x 41.3 mm)	
	with KNB-48L	2.28 x 5.02 x 1.91 in (58 x 127.5 x 48.5 mm)	
Weight (net)	Radio only	8.82 oz (250 g)	
	with KNB-47L	13.23 oz (375 g)	
	with KNB-48L	14.29 oz (405 g)	

		NX-200	NX-300
RECEIVER			
Sensitivity	Digital @ 6.25kHz (3% BER)	0.20 µV	
	Digital @ 12.5kHz (3% BER)	0.25 µV	
	Analog (12 dB SINAD)	0.25 µV	
Selectivity	Analog @ 25 kHz	72 dB	
	Analog @ 12.5 kHz	65 dB	
Intermodulation Distortion	Analog	70 dB (±50,100 kHz)	
Spurious Response	Analog	70 dB	
Audio Distortion		Less than 3%	
Audio Output		500 mW / 8 Ω	
TRANSMITTER			
RF Power Output		5 W / 1 W	
Spurious Response		70 dB	
FM Hum & Noise	Analog @ 25 kHz	45 dB	
	Analog @ 12.5 kHz	40 dB	
Audio Distortion		Less than 3%	
Modulation		16K0F3E, 11K0F3E, 8K30F1E, 8K30F1D, 8K30F7W, 4K00F1E, 4K00F1D, 4K00F7W, 4K00F2D	

Analog measurements made per TIA/EIA 603 and specifications shown are typical. Kenwood reserves the right to change specifications without prior notice or obligation.

FleetSync® is a registered trademark of Kenwood Corporation.
LIR® is a registered trademark of Transcrypt International.
AMBE+2™ is a trademark of Digital Voice Systems Inc.
Windows™ is a registered trademark of Microsoft Corporation.
NXDN™ is a trademark of Kenwood Corporation and Icom Inc.
NEXEDGE™ is a trademark of Kenwood Corporation.

Applicable MIL-STD & IP

MIL Standard	MIL 810C Methods/Procedures	MIL 810D Methods/Procedures	MIL 810E Methods/Procedures	MIL 810F Methods/Procedures
Low Pressure	500.1/Procedure I	500.2/Procedure I, II	500.3/Procedure I, II	500.4/Procedure I, II
High Temperature	501.1/Procedure I, II	501.2/Procedure I, II	501.3/Procedure I, II	501.4/Procedure I, II
Low Temperature	502.1/Procedure I	502.2/Procedure I, II	502.3/Procedure I, II	502.4/Procedure I, II
Temperature Shock	503.1/Procedure I	503.2/Procedure I	503.3/Procedure I	503.4/Procedure I, II
Solar Radiation	505.1/Procedure I	505.2/Procedure I	505.3/Procedure I	505.4/Procedure I
Rain	506.1/Procedure I, II	506.2/Procedure I, II	506.3/Procedure I, II	506.4/Procedure I, III
Humidity	507.1/Procedure I, II	507.2/Procedure II, III	507.3/Procedure II, III	507.4
Salt Fog	509.1/Procedure I	509.2/Procedure I	509.3/Procedure I	509.4
Dust	510.1/Procedure I	510.2/Procedure I	510.3/Procedure I	510.4/Procedure I, III
Vibration	514.2/Procedure VIII, X	514.3/Procedure I	514.4/Procedure I	514.5/Procedure I
Shock	516.2/Procedure I, II, V	516.3/Procedure I, IV	516.4/Procedure I, IV	516.5/Procedure I, IV
International Protection Standard				
Dust & Water Protection	IP54			
	IP55			

Listen to the Future

Kenwood has always connected with people through sound. Now we want to expand the world of sound in ways that only Kenwood can, listening to our customers and to the pulse of the coming age as we head toward a future of shared discovery, inspiration and enjoyment.

Kenwood U.S.A. Corporation
Communications Sector Headquarters
3975 Johns Creek Court, Suwanee, GA 30024-1265

Order Administration/Distribution
P.O. BOX 22745, 2201 East Dominguez St., Long Beach, CA 90801-5745

Kenwood Electronics Canada Inc.
Canadian Headquarters and Distribution
6070 Kestrel Road, Mississauga, Ontario, Canada L5T 1S8

Authorized Dealer

Precision Wireless Service
Two-Way Radio Solutions
(800) 772-3007

939 Shiloh Rd., Building 40, Suite 4
Windsor, CA 95492
Phone (707) 836-6855
Fax (707) 836-9120