

PRODUCT DATA SHEET i18R





i18R

SPECIFICATIONS

TIMELINE	
Earliest launch of sales	17-10-2017
Global launch date	17-10-2017
Earliest Shipping date	15-09-2017
Order date	25-07-2017

TECHNICAL DATA	
Length defocused [mm]	171
Length focused [mm]	178
Head diameter [mm]	86
Tube diameter [mm]	47
Weight incl. batteries [g]	620
Weight without batteries [g]	470
Focus function	Yes
Head material	Aluminum alloy
Tube material	Aluminum alloy
Optic	Plastic lense (PMMA)
Cartridge	No

POWER SUPPLY Power source type Rechargeable battery Battery quantity 1 Li-ion Battery type Battery description 3x18650 Battery Pack 3.7V Total battery voltage [V] 3.7 10200 Total battery capacity [mAh] Total battery energy² [Wh] 37.74 Rechargeable Yes Charging time⁵ [min] 480 Charging technology Internal Energy modes Constant Current, Energy Saving

FURTHER SPECIFICATIONS IP class IPX4 Drop test (drop height) [m] 1 Working temperature range [°C] -20 to +40

Battery Indicator, Charge Indicator

Energy status indicator

LIGHT FUNCTIONS

Power, Mid Power, Low Power, Strobe

LIGHT SOURCE	
Amount LEDs	3
Color	White
Color temperature [K]	6000 to 8000
Color rendering index (CRI)	65

LIGHT VALUES				
	Boost	Power	Mid Power	Low Power
Light output ¹ [lm]		3000	600	30
Beam distance ¹ [m]		540	260	80
Run time ¹ [h]		5	9	96

SWITCH

Front Switch

FEATURES

Transportation lock

TECHNOLOGIES

Advanced Focus System³, Temperature Control System, Rapid Focus, X-Lens Technology, Smart Light Technology





—i18R

ACCESORIES

PRODUCT CATEGORY	ITEM NUMBER PRODUCT NAME		
Color filter / Signal caps	501507	Color Filter Blue 85.5mm	
Color filter / Signal caps	501508 Color Filter Red 85.5mm		
Color filter / Signal caps	501509	09 Color Filter Green 85.5mm	
Color filter / Signal caps	501510	Color Filter Yellow 85.5mm	
Charger / Cable	0386	Car Charger	

