

4022 Mains power supply 24V

Part Number	Packaging Type	Net Weight	
BC402201	C2	4.60 kg	

Features:-

- 24 VDC output @ 18 Amp
- 88 to 264 AC 60/50 Hz input (auto ranging)
- No-break battery backup facility
- Full protection
- Internal speaker



BC402201



SA-42020



SA-45010



SA-00020



BCM40220

Note :- See brochure for more detailed information.

Includes:-

IEC mains cord UK, European, AUS, JP and US style

SA-00020

Power cable - 4022 to 4050

SA-42020

Speaker cable

SA-45010

4022 Mains power supply operation manual

BCM40220

Battery backup cable 3 metres - for 4022 Power supply

Part Number	Packaging Type	Net Weight	
BCA402201	C4	1.05 kg	

To connect external battery for no-break battery backup in case of AC supply failure.

Includes:-

- Universal battery lugs


100 Ah 12 V sealed solar block battery - air-freightable

BCA92203	N/A	32 kg	
----------	-----	-------	--

For no-break battery backup in case of AC supply failure.


Cabling kit for paralleling batteries - per additional battery, consists of two heavy duty cables with lugs and two battery lugs

BCA92208	C4	0.35 kg	
----------	----	---------	--

To parallel several batteries as above to increase the battery backup time in case of AC supply failure.

