



This adaptable mobile radio supports both NXDN and DMR digital protocols as well as mixed digital & FM analog operation, enabling it to serve with distinction in a wide range of enterprise- and operation-critical applications. Designed with flexibility in mind, it's packed with convenient features like Bluetooth® for hands-free operation and built-in GPS. And providing greater freedom of installation, the radio's front panel can be used as a remote control head (this requires an optional upgrade, to be available in future). Additionally, for expansion capability a software license certification system facilitates extensive customization.

PRODUCT HIGHLIGHTS

- **Multi-protocol digital** radio: Designed to operate under an NXDN or DMR digital, and FM analog protocols
- **NXDN** Conventional and Type-C & Gen2 Trunking
- **DMR** Tier II & Site Roaming
- **Mixed Digital & FM Analog Operation** allows gradual migration at your own pace
- **4-Line** Basic Frame (2-line Main/Sub-LCD, icon, & key guide) / 14 Characters
- **4-Line** Text Message Frame (2 Lines of Text, icon & key guide) Note: The number of lines may vary depending on the display language (character set).
- **7-Color** LED indicator
- External and Internal Speaker Switching
- **Built-in GPS Receiver** for effective fleet management
- **Built-in Bluetooth** for hands-free operation – Applicable Bluetooth profiles: HSP (Headset Profile provided) and SPP (Serial Port Profile available as an option; availability depends on the model)
- Renowned **KENWOOD Audio Quality** with **Active Noise Reduction (ANR)** that utilizes built-in DSP
- Software **DES** and **AES** Encryptions for **NXDN** Conventional/Trunking and **DMR** Conventional protocols
- **IP54** and **MIL-STD-810 C/D/E/F/G**

GENERAL FEATURES

- Audio Output Power (4 Watts at 4 ohms)
- 512 CH/128 Zones
- 1000 CH option
- Paging Call
- Emergency Call
- Status/Text Message
- Remote Stun/Kill/Check

DIGITAL - NXDN MODE

- NXDN Type-C & Gen2 Trunked
- NXDN Conventional
- 6.25 & 12.5 kHz Channels
- All Group Call
- Over-the-Air Alias (OAA)
- Over-the-Air Programming (OTAP)

DIGITAL - DMR MODE

- Complies with ETSI DMR Tier II standards
- 12.5 kHz Two-slot TDMA channels
- Call Interruption
- Dual-slot Direct Mode
- ARC4 Encryption
- Energy Efficient

ANALOG - FM MODE

- Conventional & LTR Trunking
- FleetSync/II: PTT ID ANI / Caller ID Display, Selective Group Call, Emergency Status / Text Messages
- MDC-1200: PTT ID ANI / Caller ID Display, Emergency, Radio Check / Inhibit
- QT / DQT, DTMF, 5-Tone
- Built-in Voice Inversion Scrambler



OPTIONAL ACCESSORIES

- **KMC-53**
DESKTOP MICROPHONE
(Tuned for NXDN;
no support for TDMA)



- **KES-3**
EXTERNAL SPEAKER
(compact low profile;
3.5 mm plug)



- **KCT-18**
IGNITION SENSE
CABLE
(requires KCT-60)



- **KCT-60**
CONNECTION CABLE
(D-sub 15 to Molex
15 Pin Connector)



- **KRA-40G**
GPS ACTIVE ANTENNA



- **KMC-35/36**
IP54/55 MICROPHONE
(without/with 12-keypad)



- **KES-5** EXTERNAL
SPEAKER (40 W max
input, requires KCT-60)



- **KCT-23**
DC POWER CABLE



- **KLF-2**
LINE FILTER



- **KPG-180AP**
OTAP MANAGER

- **KMB-10**
KEY LOCK
ADAPTER



All accessories and options may not be available in all markets.
Contact an authorized KENWOOD dealer for details and complete list of all accessories and options.

SPECIFICATIONS

GENERAL		NX-3720(G)	NX-3820(G)
Frequency Range		136-174 MHz	400-470 MHz
Max. Channels per Radio		Up to 1000 channels with option	
Number of Channels		512	
Number of Zones		128	
Channel Spacing	Analog	12.5/20/25 kHz	
	Digital	6.25/12.5 kHz	
Operating Voltage		13.2 VDC (10.8 ~ 15.6 VDC)	
Current Drain	Standby	0.45 A	
	RX	2.3 A	
	TX	9 A	
Operating Temperature		-30°C to +60°C	
Frequency Stability		± 1.0 ppm	
Antenna Impedance		50 Ohms	
Dimensions (W x H x D) Radio with Control Head *Projections not included		160 x 43 x 160 mm	
Weight (net) Radio with Control Head		1.2 kg	
Applicable Standards	ETSI (EMC)	EN 301 489-3, EN 301 489-5, EN 301 489-17	
	ETSI (Spectrum)	EN 300 086, EN 300 113, EN 300 219, EN 300 328, EN 300 440, EN 301 166	
	ETSI Safety	EN 60215, EN 60950-1, EN 62368-1	

Specifications are measured according to applicable standards.
Specifications shown are typical and subject to change without notice, due to advancements in technology.

RECEIVER		NX-3720(G)	NX-3820(G)
Sensitivity	NXDN 3 % BER (6.25 kHz/12.5 kHz)	0.20 µV / 0.28 µV	
	NXDN 1 % BER (6.25 kHz/12.5 kHz)	-5.0 dBµV (0.28 µV) / -2 dBµV (0.40 µV)	
	DMR 12.5 kHz Digital, 5 % BER	-4.5 dBµV (0.30 µV)	
	DMR 12.5 kHz Digital, 1 % BER	-2 dBµV (0.40 µV)	
	Analog, EIA 12 dB SINAD (12.5/20 & 25 kHz)	0.25 µV	
Selectivity	Analog, EN 20 dB SINAD (12.5/20 & 25 kHz)	-1 dBµV (0.45 µV) / -3 dBµV (0.35 µV)	
	Analog 12.5 kHz	70 dB	68 dB
	Analog 20 kHz	78 dB	76 dB
Intermodulation	Analog 25 kHz	80 dB	78 dB
	Spurious Rejection	70 dB	
Audio Distortion		80 dB	
Audio Output		2 %	
TRANSMITTER		NX-3720(G)	NX-3820(G)
RF Power Output (High / Low)		25 W / 5 W	
Spurious Emission		-36 dBm ≤1 GHz, -30 dBm >1 GHz	
FM Hum & Noise	Analog @ 25 kHz	50 dB	
	Analog @ 20 kHz	50 dB	
	Analog @ 12.5 kHz	45 dB	
Audio Distortion		2 %	
Digital Protocol		ETSI TS 102 361-1, -2, -3	
Emission Designator		16K0F3E, 14K0F2D, 14K0F3E, 12K0F2D, 8K50F3E, 8K30F1E, 8K30F1D, 8K30F7W, 7K50F2D, 7K60FXE, 7K60FXD, 4K00F1E, 4K00F1D, 4K00F7W, 4K00F2D	

APPLICABLE MIL-STD & IP

MIL Standards	Methods / Procedures				
	810C	810D	810E	810F	810G
Low Pressure	500.1/ I	500.2/ I, II	500.3/ I, II	500.4/ I, II	500.5/ I, II
High Temperature	501.1/ I, II	501.2/ I, II	501.3/ I, II	501.4/ I, II	501.5/ I, II
Low Temperature	502.1/ I	502.2/ I, II	502.3/ I, II	502.4/ I, II	502.5/ I, II
Temp. Shock	503.1/ I	503.2/ I	503.3/ I	503.4/ I, II	503.5/ I
Solar Radiation	505.1/ I	505.2/ I	505.3/ I	505.4/ I	505.5/ I
Rain*	506.1/ I, II	506.2/ I, II	506.3/ I, II	506.4/ I, III	506.5/ I, III
Humidity	507.1/ I, II	507.2/ I, III	507.3/ II, III	507.4	507.5/ II
Salt Fog	509.1/ I	509.2/ I	509.3/ I	509.4	509.5
Dust	510.1/ I	510.2/ I	510.3/ I	510.4/ I, III	510.5/ I
Vibration	514.2/ VIII, X	514.3/ I	514.4/ I	514.5/ I	514.6/ I
Shock	516.2/ I, II, V	516.3/ I, IV, V	516.4/ I, IV, V	516.5/ I, IV, V	516.6/ I, IV, V
International Protection Standards					
Dust & Water*	IP54 (Radio unit itself)				

*Microphone KMC-35 or KMC-36 must be connected to the radio, and all accessory connectors must be covered.

• The Bluetooth word mark and logos are registered trademarks owned by the Bluetooth SIG, Inc. • NXDN™ is a trademark of JVCKENWOOD Corporation and Icom Inc. • NEXEDGE® is a registered trademark of JVCKENWOOD Corporation.
• FleetSync® is a registered trademark of JVCKENWOOD Corporation. • All other trademarks are the property of their respective holders.

JVCKENWOOD U.K. Limited

12 Priestley Way, London NW2 7BA, United Kingdom

<http://kenwoodcommunications.co.uk/comm/>

<http://comms.kenwood.com/en/>



ISO9001 Registered
Communications Systems Business Unit
JVCKENWOOD Corporation

CL863E-E-2